

## BDW G



## SPECIFICATIONS

Conductor	Solid annealed copper
Insulation	Polyolefin
Core Assembly	Individual conductor dimensions are tightly controlled to limit resistance unbalance of twisted pairs; pair twist lays are varied to minimize crosstalk and meet capacitance unbalance limits
Filling Compound	Wire core is completely filled with 80°C ETPR compound, filling the air spaces between insulated conductors
Inner Jacket	Polyethylene
Shield	Corrugated, 5 mil gopher resistant armor applied longitudinally over the inner jacket and flooded
Outer Jacket	Black polyethylene
Standards Compliance	*RDUP 7 CFR 1755.860 (PE-86) ANSI/ICEA S-86-634-2011 RoHS-compliant

## PRODUCT DESCRIPTION

BDW G is a filled, double-jacketed buried wire intended for direct burial applications. Applications include distribution circuits and service entrance wires. All types are designed to withstand installation stresses. They are filled with an ETPR compound, which completely coats each insulated conductor and fills the air space between conductors. BDW G also provides protection from rodents or harsh environments. Each conductor is insulated with solid polyolefin in distinctive colors. The insulation of the tip conductor is marked with a stripe of the mating ring insulation color to reduce the possibility of splitting pairs during installation.

## FEATURES

- Polyethylene inner jacket
- Corrugated armor
- Polyethylene outer jacket

## BENEFITS

- Provides additional mechanical and moisture protection
- Gopher resistant
- Provides excellent mechanical protection
- Provides tough, flexible, protective covering that withstands exposure to sunlight, atmospheric temperatures, ground chemicals and stresses expected in standard installations

## ELECTRICAL SPECIFICATIONS

All Pairs		Average Mutual Capacitance @ 1,000 Hz nF/mile (nF/km)				
Maximum Individual		94 (58)				
Wire Average		83 ± 7 (52 ± 4)				

  

Conductor Size AWG (mm)	Minimum Insulation Resistance @ 68°F (20°C) megohm-mile (megohm-km)	Maximum Average Attenuation 772 kHz @ 68°F (20°C) dB/kft (dB/km)	Maximum Conductor Resistance @ 68°F (20°C) Ohms/mile (Ohms/km)	DC Resistance Unbalance Maximum % Individual Pair	Dielectric Strength Minimum Volts DC	
					Conductor to Conductor	Conductor to Shield
22 (0.64)	1,000 (1,600)	4.4 (14.4)	91 (56.4)	5.0	5,000	20,000
24 (0.51)	1,000 (1,600)	5.5 (18.0)	144 (89.5)	5.0	4,000	20,000

  

Minimum NEXT @ 722 kHz	Crosstalk Loss dB/kft (dB/km)	Capacitance Unbalance @ 1,000 Hz pF @ 1 kft (pF @ 1 km)	
		44 (144)	Maximum Individual Pair to Pair
		Maximum Individual Pair to Ground	800 (2,625)

## PART NUMBERS AND PHYSICAL CHARACTERISTICS

Part Number	Pair Count	AWG (mm)	Nominal Diameter in (mm)	Approx. Weight lbs/kft (kg/km)	Standard Length ft (m)	Package
04-052-17	2	22 (0.64)	0.32 (8.1)	55 (80)	1,000 (305)	Reel
04-053-17	2	22 (0.64)	0.32 (8.1)	55 (80)	2,500 (762)	Reel
04-055-17	2	22 (0.64)	0.32 (8.1)	55 (80)	5,000 (1,524)	Reel
04-056-17	3	22 (0.64)	0.33 (8.4)	60 (90)	1,000 (305)	Reel
04-057-17	3	22 (0.64)	0.33 (8.4)	60 (90)	2,500 (762)	Reel
04-058-17	3	22 (0.64)	0.33 (8.4)	60 (90)	5,000 (1,524)	Reel
04-067-16*	6	22 (0.64)	0.40 (10)	90 (135)	1,000 (305)	Reel
04-062-16*	6	22 (0.64)	0.40 (10)	90 (135)	2,500 (762)	Reel
04-057-16*	6	22 (0.64)	0.40 (10)	90 (135)	5,000 (1,524)	Reel
04-094-16	2	24 (0.51)	0.27 (6.9)	40 (60)	5,000 (1,524)	Reel
04-091-16	3	24 (0.51)	0.29 (7.4)	45 (65)	5,000 (1,524)	Reel

